

# PLL & UHF ANTENNA DIVERSITY SINGLE CHANNEL SYSTEM

## SYSTEM FEATURES

- ※ 16 Selectable UHF channel
- ※ Adopt PLL-Synthesized control technic
- ※ LCD information display
- ※ Balanced XLR and unbalanced 1/4" outputs



PLL 16CH

# WR-35 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

## WR-35



### RECEIVER SPECIFICATIONS

RF Frequency Range:460-970MHz  
 Image & Squirious Rejection:>70dB  
 Receiving Sensitivity:-105dBm  
 Signal/Noise Ratio:-105dB  
 Border Upon Channel Rejection>70dB  
 T.H.D.:<1%  
 Audio Output Level:0-300mV  
 Power Requirements:13-15V DC nominal 300mA  
 Dimensions:18.5x14.5x4.3cm

## HT-35/HT-35A



### HANDHELD TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz  
 RF Output:>10dBm  
 Modulation Type:FM  
 Max Deviation:±40KHz  
 Spurious Emission:>55dBc  
 Nominal Current Drain:<40mA  
 Power Requirements:2x1.5V AA  
 HT-35 Dimensions:23.5x5x5cm  
 HT-35A Dimensions:25x5.1x5.1cm

## PT-35



### BODYPACK TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz  
 RF Output:>10dBm  
 Modulation Type:FM  
 Max Deviation:±40KHz  
 Spurious Emission:>53dBc  
 Nominal Current Drain:<40mA  
 Power Requirements:2x1.5V AA  
 Dimensions:10.5x6.5x3cm

## HANDHELD



## LAVALIER



## HEADWORN



## GUITAR/BASS

