

UHF SINGLE CHANNEL SYSTEM

SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Single channel operation
- ※ Extreme low THD and super fidelity
- ※ Switch impact noise defeat circuit
- ※ Double squelch operation circuit, higher efficient and much more steady.
- ※ Unbalanced 1/4" output.



KRU-200 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

KRU-200



RECEIVER SPECIFICATIONS

RF Frequency Range:460-970MHz
 Frequency Stabilization:10PPM
 Receiving Sensitivity:-107dB(S/N:-12dB,15KHz)
 RF Image Spurious Rejection:>75dB
 Border Upon Channel Rejection:90dB
 Power Requirements:13-15V DC nominal 300mA
 Dimensions:17.8x11.8x4cm

KST-3U/KST-5U



HANDHELD TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
 Frequency Stabilization:10PPM
 RF Output Power:10dBm
 RF Spurious Emission:>60dBc
 Max Deviation:>40KHz
 Battery Voltage:9V DC
 Max Drain at 9V DC:<38mA
 KST-3U Dimensions:24x5x5cm
 KST-5U Dimensions:23.5x5x5cm

KLT-9U



BODYPACK TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
 Frequency Stabilization:10PPM
 RF Output Power:10dBm
 RF Spurious Emission:>60dBc
 Max Deviation:>40KHz
 Battery Voltage:9V DC
 Max Drain at 9V DC:<38mA
 Dimensions:8.2x6x2.3cm

HANDHELD

Receiver:KRU-200
 Handheld Mic:KST-3U or KST-5U



LAVALIER

Receiver:KRU-200
 Bodypack Transmitter:KLT-9U
 Lavalier Mic:LT-4C



HEADWORN

Receiver:KRU-200
 Bodypack Transmitter:KLT-9U
 Headworn Mic: HT-1C



GUITAR/BASS

Receiver:KRU-200
 Bodypack Transmitter:KLT-9U
 Guitar Cable:G-05C

