

# UHF DUAL CHANNEL SYSTEM

## SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Dual channel operation
- ※ Extreme low THD and super fidelity
- ※ Switch impact noise defeat circuit
- ※ Double squelch operation circuit, higher efficient and much more steady.
- ※ Balanced XLR and unbalanced 1/4" outputs.
- ※ EIA standard 19 inch housing with rack ear.



19-inch Audio equipment rack

# KRU-206 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

## KRU-206



### RECEIVER SPECIFICATIONS

RF Frequency Range:460-970MHz
Receiving Sensitivity:-105dBm(S/N:-12dB 25KHz)
Image & Spurious Rejection:>70dB
Signal/Noise Ratio:>85dB
Border Upon Channel Rejection:>70dB
T.H.D.:<0.5%
Audio Output Level:0- ± 300mV
Power Requirements:13-15V DC nominal 300mA
Dimensions:39.5x19.8x4.4cm

## KST-5U



### HANDHELD TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
RF Output:10dBm
Modulation Type:FM
Max Deviation: ± 40KHz
Spurious Emission:>55dBc
Nominal Current Drain:<40mA
Power Requirements:9V DC
Dimensions:23x5x5cm

## KLT-8U



### BODYPACK TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
RF Output:10dBm
Modulation Type:FM
Max Deviation: ± 40KHz
Spurious Emission:>53dBc
Nominal Current Drain:<40mA
Power Requirements:9V DC
Dimensions:10.5x6.5x2.5cm

## HANDHELD



Receiver:KRU-206  
Handheld Mic:KST-5U



## LAVALIER



Receiver:KRU-206  
Bodypack Transmitter:KLT-8U  
Lavalier Mic:LT-4A



## HEADWORN



Receiver:KRU-206  
Bodypack Transmitter:KLT-8U  
Headworn Mic: HT-9A



## GUITAR/BASS



Receiver:KRU-206  
Bodypack Transmitter:KLT-8U  
Guitar Cable:G-05



## DUAL CHANNEL COMBO



Receiver:KRU-206  
Handheld Mic:KST-5U  
Bodypack Transmitter:KLT-8U  
Lavalier Mic:LT-4A  
Headworn Mic: HT-9A  
Guitar Cable:G-05