

UHF FOUR CHANNEL SYSTEM

SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Four channel operation
- ※ Balanced XLR and unbalanced 1/4" outputs

WR-15&4 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM



WR-15&4



RECEIVER SPECIFICATIONS

RF Frequency Range: 460-970MHz
 Image & Spurious Rejection: >70dB
 Receiving Sensitivity: -105dBm
 Signal/Noise Ratio: -105dB
 Border Upon Channel Rejection >70dB
 T.H.D.: <1%
 Audio Output Level: 0-300mV
 Power Requirements: 13-15V DC nominal 1000mA
 Dimensions: 39.4x23.5x5.5cm

HT-15/HT-15A



HANDHELD TRANSMITTER SPECIFICATIONS

RF Frequency Range: 460-970MHz
 RF Output: >10dBm
 Modulation Type: FM
 Max Deviation: ±40KHz
 Spurious Emission: >55dBc
 Nominal Current Drain: <40mA
 Power Requirements: 2x1.5V AA
 HT-15 Dimensions: 23.5x5x5cm
 HT-15A Dimensions: 25x5.1x5.1cm

PT-15



BODYPACK TRANSMITTER SPECIFICATIONS

RF Frequency Range: 460-970MHz
 RF Output: >10dBm
 Modulation Type: FM
 Max Deviation: ±40KHz
 Spurious Emission: >53dBc
 Nominal Current Drain: <40mA
 Power Requirements: 2x1.5V AA
 Dimensions: 10.5x6.5x3cm

HANDHELD

Receiver: WR-15&4
 Handheld Mic: HT-15/HT-15A



LAVALIER

Receiver: WR-15&4
 Bodypack Transmitter: PT-15
 Lavalier Mic: LT-4A



HEADWORN

Receiver: WR-15&4
 Bodypack Transmitter: PT-15
 Headworn Mic: HT-9A



GUITAR/BASS

Receiver: WR-15&4
 Bodypack Transmitter: PT-15
 Guitar Cable: G-05



FOUR CHANNEL COMBO

